

LAMAR

UTILITY TRAILERS



THE HASSLE-FREE TRAILER EXPERIENCE

THE **HASSLE-FREE** TRAILER EXPERIENCE



3 Year Structural Warranty

Lamar's warranty covers the primary frame for 3 years.

1 Year Component Warranty

Non wearing components are covered for 1 year.

Premium 3rd Party Component Warranty

Lamar uses high quality brands for parts and the warranty is covered by the parts respective manufacturer.

UTILITY TRAILER

3,000 - 7,000 LB. GVWR

MODEL: UC



GVWR: 3,000 - 7,000 lbs.
Weight : 1,000 - 1,500 lbs.
Payload: 2,000 - 5,500 lbs.

Lengths: 10' - 18'
Widths: 60" - 83"
Frame: 4" Channel

Floor: Treated Pine
Deck Height: 20"
Loading Angle: 24°

Whether you're hauling lawn mowers, ATV's, or camping gear, the UC single axle is a commercial-grade choice for homeowners and small business owners. Your mid-sized tow vehicle won't skip a beat. Tandem axles offer more payload and better control. Perfect for larger mid-sized vehicle or 1/2 tons.



UC13/UC15

STANDARD FEATURES

Axles: 3.5K EZ Lube Idler Spring Axle

5.2K EZ Lube Idler Spring Axles

3.5K EZ Lube Idler & Elec Brake Spring Axles

Coupler: 2" 10K Demco Adj Cast Coupler

Crossmembers: 24" Center-to-Center

Dove: Straight Deck

Fenders: Round Diamond Plate | Diamond Teardrop

Floor: Treated Pine

Frame: 4" Channel

Hitch: Bumper Pull

Jack: 2K Top-Wind Flip Jack

Ramps: 4' Spring Assisted Laydown Gate | Pair of Slide In Ramps

Spare: Spare Tire Mount

Tie Downs: Standard Stake Pockets

Tires: 225/75 R15 (D) 8Ply | 205/75 R15 (C) 6Ply

POPULAR UPGRADES

- FRONT TOOLBOX
- EXTRA STAKE POCKETS
- D-RINGS
- 3' SPRING ASSIST. GATE
- 2x2" SQ. TUBE TOP RAIL



UTILITY TRAILER

10,000 LB. GVWR

MODEL: U5



GVWR: 10,000 lbs.

Weight : 1,800 - 2,800 lbs.

Payload: 8,000 - 13,000 lbs.

Lengths: 12' - 24'

Widths: 77" - 83"

Frame: 5" Channel

Floor: Treated Pine

Deck Height: 22"

Load Angle: 22°

A great match for mid-sized equipment and tractors, the U5 is the workhorse utility trailer. Concrete and construction companies love its heavy duty 5" frame. 1/2 ton recommended for hauling.



U525

STANDARD FEATURES

Axles: 5.2K EZ Lube Idler & Elec Brake Spring Axles

Coupler: 2 5/16" 21K Demco Adj Cast Coupler

Crossmembers: 24" Center-to-Center

Dove: Straight Deck

Fenders: Diamond Plate

Floor: Treated Pine

Frame: 5" Channel

Hitch: Bumper Pull

Jack: 7K Drop-Leg Jack

Ramps: Slide In Ramps (12'-16') | Side Slide In Ramps (18'+)

Tie Downs: Standard Stake Pockets

Tires: 235/80 R16 (E) 10Ply

POPULAR UPGRADES

- 3x3" SQ. TUBE TOP RAIL
- 5' HEAVY DUTY GATE
- 2 BRAKES
- 2' DOVE
- SPARE TIRE



UTILITY TRAILER

MODEL: U6

14,000 - 16,000 LB. GVWR



GVWR: 14,000 - 16,000 lbs.

Weight : 2,400 - 3,300 lbs.

Payload: 10,750 - 13,400 lbs.

Lengths: 12' - 26'

Widths: 77" - 83"

Frame: 6" Channel

Floor: Treated Pine

Deck Height: 25"

Loading Angle: 25°

Built for hauling larger equipment and tractors, the U6 steps up with a 6" frame for added strength and reliability. $\frac{3}{4}$ ton recommended for towing.



U627/U628

STANDARD FEATURES

Axles: 7K EZ Lube Elec Brake | 8K Elec Brake Oil Bath

Coupler: 2 5/16" 21K Demco Adj Coupler

Crossmembers: 16" Center-to-Center

Dove: Straight Deck

Fenders: Diamond Plate

Floor: Treated Pine

Frame: 6" Channel

Hitch: Bumper Pull

Jack: Single 10K Drop-Leg Jack

Ramps: Side Slide In (12'-16') | Rear Slide In Ramps (18'+)

Tie Downs: Standard Stake Pockets

Tires: 215/75 R17.5 (H) 16Ply SS | 238/80 R16 (E) 10Ply

POPULAR UPGRADES

- 5' HEAVY DUTY GATE
- 24" STAND UP RAMPS
- 2' DOVE
- SPARE MOUNT
- 3x3" SQ. TUBE TOP RAIL



UTILITY TRAILER

MODEL: US

3,500 - 9,990 LB. GVWR



GVWR: 3,500 - 9,990 lbs.
Weight : 1,550 - 2,150 lbs.
Payload: 1,800 - 7,850 lbs.

Lengths: 12' - 16'
Widths: 77" - 83"
Frame: 4" Channel

Floor: Treated Pine
Deck Height: 20"
Loading Angle: 24°

Keep loose items like firewood, mulch, or bagged materials secure in transit. The US features tall, solid sides and has optional landscape options that give added peace of mind. Larger mid-sized vehicles or ½ tons recommended.



US13/US15



US23/US25

STANDARD FEATURES

Axles: 3.5K EZ Lube Idler Spring Axle

5.2K EZ Lube Idler Spring Axles

3.5K EZ Lube Idler & Elec Brake Spring Axles

5.2K EZ Lube Idler & Elec Brake Spring Axles

Coupler: 2" 10K Demco Adj Cast Coupler

2 5/16" 21K Demco Adj Cast Coupler

Crossmembers: 24" Center-to-Center

Floor: Treated Pine

Frame: 4" Channel

Hitch: Bumper Pull

Jack: 2K Top-Wind Flip Jack

Gate: 4' Spring Assisted Lay-Down Gate

Tie Downs: D-Rings & Stake Pockets

Tires: 205/75 R15 (C) 6Ply | 225/75 R15 (D) 8Ply

POPULAR UPGRADES

- TRIMMER RACK
- WATER COOLER RACK
- FUEL CAN RACK
- TOOLCAGE
- TOOLBOX





HONOR **GOD**



SERVE **HUMBLY**



KEEP IT **SIMPLE**

903-782-9333 | info@lamartrailers.com
7271 FM 38 N. Sumner, Texas 75486



L A M A R T R A I L E R S . C O M