



UTILITY TRAILERS



THE HASSLE-FREE TRAILER EXPERIENCE

**LESS
HASSLE.**

**MORE
CONFIDENCE.**

THE HASSLE-FREE TRAILER EXPERIENCE

BACKED FOR 10 YEARS.



10 Year Structural Warranty

Lamar's warranty covers the frame and crossmembers for 10 years.

3 Year Component Warranty

Lamar built components are covered for 3 years.

1 Year Purchased Component Warranty

Lamar uses high quality brands for parts and the warranty is covered by the parts respective manufacturer.

WE BUILD TRAILERS THAT LAST.

COMMERCIAL UTILITY UC



GVWR: 3,000 - 7,000 lbs.



Whether you're hauling lawn mowers, ATV's, or camping gear, the UC single axle is a commercial-grade choice for homeowners and small business owners. Your mid-sized tow vehicle won't skip a beat. Tandem axles offer more payload and better control. Perfect for larger mid-sized vehicle or 1/2 tons.

3

Weight: 1,000 - 1,500 lbs. | Payload: 2,000 - 5,500 lbs. | Lengths: 10' - 18' | Widths: 60" - 83"
Frame: 4" Channel | Floor: Treated Pine | Deck Height: 20" | Loading Angle: 24°

COMMERCIAL UTILITY UC



STANDARD FEATURES

- > **Axles:** 3.5K EZ Lube Idler Spring Axle
5.2K EZ Lube Idler Spring Axles
3.5K EZ Lube Idler & Elec Brake Spring Axles
- > **Coupler:** 2" 10K Demco Adj Cast Coupler
- > **Crossmembers:** 24" Center-to-Center
- > **Dove:** Straight Deck
- > **Fenders:** Round Diamond Plate | Diamond Teardrop
- > **Floor:** Treated Pine
- > **Frame:** 4" Channel
- > **Hitch:** Bumper Pull
- > **Jack:** 2K Top-Wind Flip Jack
- > **Ramps:** 4' Spring Assisted Laydown Gate | Pair of Slide In Ramps
- > **Spare:** Spare Tire Mount
- > **Tie Downs:** Standard Stake Pockets
- > **Tires:** 225/75 R15 (D) 8Ply | 205/75 R15 (C) 6Ply



POPULAR UPGRADES

Front Toolbox | Extra Stake Pockets | D-Rings | 3' Spring Assisted Gate | 2x2" Sq. Tube Top Rail

HEAVY DUTY UTILITY U5



GVWR: 10,000 lbs.



A great match for mid-sized equipment and tractors, the U5 is the workhorse utility trailer. Concrete and construction companies love its heavy duty 5" frame. 1/2 ton recommended for hauling.

5

Weight: 1,800 - 2,800 lbs. | Payload: 8,000 - 13,000 lbs. | Lengths: 12' - 24' | Widths: 77" - 83"
Frame: 5" Channel | Floor: Treated Pine | Deck Height: 22" | Loading Angle: 22°

HEAVY DUTY UTILITY U5



SCAN FOR
MORE INFO

STANDARD FEATURES

- > **Axles:** 5.2K EZ Lube Idler & Elec Brake Spring Axles
- > **Coupler:** 2 5/16" 21K Demco Adj Cast Coupler
- > **Crossmembers:** 24" Center-to-Center
- > **Dove:** Straight Deck
- > **Fenders:** Diamond Plate
- > **Floor:** Treated Pine
- > **Frame:** 5" Channel
- > **Hitch:** Bumper Pull
- > **Jack:** 7K Drop-Leg Jack
- > **Ramps:** Slide In Ramps (12'-16') | Side Slide In Ramps (18'+)
- > **Tie Downs:** Standard Stake Pockets
- > **Tires:** 235/80 R16 (E) 10Ply



POPULAR UPGRADES

3x3" Sq. Tube Top Rail | 5' Heavy Duty Gate | 2 Brakes | 2' Dove | Spare Tire

6

EXTREME DUTY U6



GVWR: 14,000 - 16,000 lbs.



Built for hauling larger equipment and tractors, the U6 steps up with a 6" frame for added strength and reliability. $\frac{3}{4}$ ton recommended for towing.

7

Weight: 2,400 - 3,300 lbs. | Payload: 10,750 - 13,400 lbs. | Lengths: 12' - 26' | Widths: 77" - 83"
Frame: 6" Channel | Floor: Treated Pine | Deck Height: 25" | Loading Angle: 25°

EXTREME DUTY U6



SCAN FOR
MORE INFO

STANDARD FEATURES

- > **Axles:** 7K EZ Lube Elec Brake | 8K Elec Brake Oil Bath
- > **Coupler:** 2 5/16" 21K Demco Adj Coupler
- > **Crossmembers:** 16" Center-to-Center
- > **Dove:** Straight Deck
- > **Fenders:** Diamond Plate
- > **Floor:** Treated Pine
- > **Frame:** 6" Channel
- > **Hitch:** Bumper Pull
- > **Jack:** Single 10K Drop-Leg Jack
- > **Ramps:** Side Slide In Ramps (12'-16') | Rear Slide In Ramps (18'+)
- > **Tie Downs:** Standard Stake Pockets
- > **Tires:** 215/75 R17.5 (H) 16Ply SS | 235/80 R16 (E) 10Ply



POPULAR UPGRADES

5' Heavy Duty Gate | 24" Stand Up Ramps | 2' Dove | Spare Mount | 3x3" Sq. Tube Top Rail

SOLID SIDE UTILITY US



GVWR: 3,500 - 9,990 lbs.



Keep loose items like firewood, mulch, or bagged materials secure in transit. The US features tall, solid sides and has optional landscape options that give added peace of mind. Larger mid-sized vehicles or ½ tons recommended.

9

Weight: 1,550 - 2,150 lbs. | Payload: 1,800 - 7,850 lbs. | Lengths: 12' - 26' | Widths: 77" - 83"
Frame: 4" Channel | Floor: Treated Pine | Deck Height: 20" | Loading Angle: 24°

SOLID SIDE UTILITY US



SCAN FOR
MORE INFO

STANDARD FEATURES

- > **Axles:** 3.5K EZ Lube Idler Spring Axle
5.2K EZ Lube Idler Spring Axles
3.5K EZ Lube Idler & Elec Brake Spring Axles
5.2K EZ Lube Idler & Elec Brake Spring Axles
- > **Coupler:** 2" 10K Demco Adj Cast Coupler
2 5/16" 21K Demco Adj Cast Coupler
- > **Crossmembers:** 24" Center-to-Center
- > **Floor:** Treated Pine
- > **Frame:** 4" Channel
- > **Gate:** 4' Spring Assisted Lay-Down Gate
- > **Hitch:** Bumper Pull
- > **Jack:** 2K Top-Wind Flap Jack
- > **Tie Downs:** D-Rings & Stake Pockets
- > **Tires:** 205/75 R15 (C) 6Ply | 225/75 R15 (D) 8Ply



POPULAR UPGRADES

Trimmer Rack | Water Cooler Rack | Fuel Can Rack | Toolcage | Toolbox

10

LAMAR **T R A I L E R S**

903-782-9333 | info@lamartrailers.com

7271 FM 38 N. Sumner, Texas 75486



**READ OUR
GOOGLE REVIEWS**



**FIND A DEALER
LOCATED NEAR YOU**

TRAILERS THAT LAST. PEOPLE WHO CARE. FOR GOD'S GLORY.